PRICE LIST - IIIA

Control Valves for AHU'S

Modulating Control, PN10 **Effective from 1st November, 2026**

S. No	DESCRIPTION	MODEL	PRICE (Rs. each)
1 .	2/3 way Control Valve (CI Body) with linkage Set, PN1 0		
	• 20mm	3S-20	3,200.00
	• 25mm	3S-25	3,200.00
	• 32mm	3S-32	4,300.00
	• 40mm	2S-40	3,600.00
	• 40mm	3S-40	4,700.00
	• 50mm	2S-50	5,250.00
	• 50mm	3S-50	6,500.00
	• 65mm	2F-65	8,850.00
	• 65mm	3F-65	11,350.00
	• 80mm	2F-80	13,200.00
	• 80mm	3F-80	16,000.00
	• 1 00mm	2F-1 00	16,750.00
	• 1 00mm	3F-1 00	20,750.00
	• 1 25mm	2F-1 25	20,000.00
	• 1 25mm	3F-1 25	26,000.00
2.	Rotary Actuators modulating for Control Valves 24Vac/dc, 0-1 0Vdc input,2-1 0Vdc feedback,Form Fit		
	• 5Nm for (20mm, 25mm, 32mm)	ARM-05-24F.V	3,750.00
	• 1 0Nm for (40mm,50mm)	ARM-1 0-24F.V	4,800.00
	• 20Nm for (65mm, 80mm, 1 00mm,1 25mm)	ARM-20-24F.V	5,600.00
3.	Microprocessor Based Controller with LCD display, 24vac, range 1 5°C-35°C,0-1 0Vdc output.	C-2A-T1 -V-X	2,950.00
	OR		
	Microprocessor Based Controller with LCD display, 24vac, range 1 5°C-35°C,0-1 0Vdc output & external sensor	C-2A-T1 -V-E1	3,150.00
	• Extra for Temp. Sensor Bulb Type with Cable Gland	S-X-B4-T1 .G	580.00
4.	Microprocessor Based Controller with LCD display, 24vac, range 1 5°C-35°C,2-1 0 Vdc I nput (BMS), 0-1 0Vdc output.	C-2A-T1 -V-B	3,250.00
5.	Power Supply 230Vac input, 24Vac output, 300mA (1 no. required per controller)	P-1 6-2-3	680.00

NOTE: Controller Model C-2A-T1 -VB can modulate our valve independently through temp.sensor provided. I f the BMS is available it can accept 2-1 0Vdc signafrom BMS and can operate the valve according to BMS signal, whenever BMS signal fails it reverts back to independent operation.











GST extra, as applicable.
for other Terms & Conditions, please refer : http: //anergy. in/Commercial/Terms_Conditions. pdf

Anergy Instruments Pvt. Ltd.
40, Sector 27A
Faridabad - 121 003
India.
Tel : +91 129 4045901
87500 55209
Email : info@anergy.in
Web : www.anergy.in